

# Oscilla<sup>®</sup> SM910 Screening Audiometer



**\* Pulse tone \***  
**\* Easy to operate \***

# SPECIAL FEATURES

Pulse tone.  
Very readable displays.  
Noise free push buttons.  
11 frequencies: 125 Hz - 8000 Hz.  
Calibration without entering the cabinet.

**Oscilla® SM910 Screening audiometer** is a modern manual audiometer, which you may learn to operate within a few seconds.

Design as well as advanced technology has been enforced, and by means of processor controlled technique, the **Oscilla® SM910 Screening audiometer** is still made for the future. For the tone generator is used technology, which assures a 100% stable tone without any delay or distortion.

Aluminium cabinet provides a neat product, which at the same time is very sturdy and protects in the best way against any environmental influences from other electronic equipment; as aluminium protects against electromagnetic interference.

## Technical specifications:

Frequencies: 11 frequencies from 125 Hz to 8000 Hz.  
Hearing Level Range: -10 dB to 90 dB in 5 dB increments.

## Maximum intensities:

Frequencies Hz	125	250	500	750	1000	1500	2000	3000	4000	6000	8000
Air conduction dB	50	70	90	90	90	90	90	90	90	80	70

**Program:** Manual test.  
**Calibration:** Calibration data stored in programmable memory. (EN60645-1).  
**Power supply:** Mains adapter 12V AC (220-240V).  
**Dimensions:** 225mm x 180mm x 55mm.  
**Weight:** 650g. (unit only).  
**Standard accessories:** Peltor noise reducing headset including earphones, patient response, mains adapter.  
**Optional extras:** Carrying bag.